



FLEXIBLE SILICONE RUBBER SLEEVE

UL CERTIFIED NON-HEAT SHRINK RoHS COMPLIANT HI TEMPERATURE

SIL-200 is a high temperature resistant silicone rubber tube. This highly flexible tube is extremely stable and has a high arc resistance.

SIL-200 Applications

This product is used in various applications such as protection in household electrical appliances, industrial electric appliances, lighting, machinery, and electronic instruments where components are exposed to high temperatures.

Characteristics

Operating Temperature: -60° to 200° Celsius

Environmentally Friendly

Colors: Only white is UL certified

Standard Packages Available in Black & White, Colors Available Upon Request

Ordering Information

Product is supplied on spools.

Specifications

Gamma	Specifications						
Part No.	Inner Diameter		Wall Thickness Per Voltage Rating				Std.
W/ Size	Mm	Inch	WT 2500V (mm)	WT 4000V (mm)	WT 6000V (mm)	WT 7000V (mm)	Spool Size
SIL-200-8	0.8	0.031	0.5	1.0	1.5	2.0	500'
SIL-200-1	1	0.039	0.5	1.0	1.5	2.0	500'
SIL-200-1.5	1.5	0.059	0.5	1.0	1.5	2.0	500'
SIL-200-2	2	0.079	0.5	1.0	1.5	2.0	250'
SIL-200-2.5	2.5	0.098	0.5	1.0	1.5	2.0	250'
SIL-200-3	3	0.118	0.5	1.0	1.5	2.0	250'
SIL-200-3.5	3.5	0.137	0.5	1.0	1.5	2.0	250'
SIL-200-4	4	0.157	0.5	1.0	1.5	2.0	250'
SIL-200-4.5	4.5	0.177	0.5	1.0	1.5	2.0	250'
SIL-200-5	5	0.196	0.5	1.0	1.5	2.0	100'
SIL-200-5.5	5.5	0.216	0.5	1.0	1.5	2.0	100'
SIL-200-6	6	0.236	0.5	1.0	1.5	2.0	100'
SIL-200-6.5	6.5	0.255	0.5	1.0	1.5	2.0	100'
SIL-200-7	7	0.275	0.5	1.0	1.5	2.0	100'
SIL-200-7.5	7.5	0.295	0.5	1.0	1.5	2.0	100'
SIL-200-8	8	0.314	0.5	1.0	1.5	2.0	100'
SIL-200-9	9	0.353	0.5	1.0	1.5	2.0	50'
SIL-200-10	10	0.393	0.5	1.0	1.5	2.0	50'
SIL-200-11	11	0.432	0.5	1.0	1.5	2.0	50'
SIL-200-12	12	0.471	0.5	1.0	1.5	2.0	50'
SIL-200-13	13	0.511	0.5	1.0	1.5	2.0	50'
SIL-200-14	14	0.550	0.5	1.0	1.5	2.0	50'
SIL-200-15	15	0.589	0.5	1.0	1.5	2.0	50'
SIL-200-20	20	0.785	0.5	1.0	1.5	2.0	25'

Color Code: 0=BLK, 1=BRN, 2=RED, 3=ORN, 4=YLW, 5=GRN, 6=BLU, 7=VIO, 8=GRY, 9=WHT, X=CLR

P/N Example: SIL-200-1-0 = Black 1mm ID Silicone Sleeving

Property of Gamma Electronics Inc.

www.gammaelectronics.net